

Time is money Make the most of both

Danfoss Performer® Universal Scroll Compressors are designed to serve as quick, easy replacements for most 9 to 15 ton commercial air conditioning scroll compressors. These compressors come with a bolt pattern, suction and discharge lines, and performance characteristics that match up directly with some competitors' products.





Select compressor using the product selection table below based on refrigerant, nominal capacity, connection and voltage.

Nomenclature / Model No. (as indicated on compressor's label) Refrigerant & lubricant SM: R-22, mineral oil **Evolution index** Nominal capacity in thousand Btu/h at 60 Hz, ARI conditions Version Motor protection module Applies to Connection Motor voltage code Internal overload protector 090 3: 200-230V/3~/60Hz c brazed Internal thermostat, external 115, 125, 160, 4: 380-400V/3~/50Hz & 460V/3~/60Hz protector needed 175, 185 Q

Product Selection

Refrigerant	Voltage/ Phase/ Freqency	Tons	Competitor Model Nos.		Danfoss					
					Model No.	Connection type (in. ODF brazed)	Motor protection	Code No. ¹	Weight (lbs)	Solder Sleeve Adaptor Rotolock Connections
R-22	200-230/3/60	7½		ZR94KC-TF5	SM090S3VC	11/8 x 3/4	Internal overload protector	SM090-3VI	143	7765006
		91/3	CSHA-093R CSHS-093R	ZR108KC-TF5 ZR11M3-TWC	SM115S3CC	- 1¾ x ⅓	Internal thermostat, external overload needed	SM115-3QAI	172	
		10	CSHA-100R CSHS-100R	ZR125KC-TF5 ZR12M3-TWC	SM125S3CC			SM125-3QAI	172	
		12½	CSHA-125R	ZR16M3-TWC ZR16M3-TW5 ZR160KC-TWD	SM160T3CC	15/s x 11/s		SM160-3CBI	198	7765028
		14	CSHA-140R CSHS-140R		SM175S3CC			SM175-3QAI	220	
		15	CSHA-150R CSHS-150R	ZR190KC-TW5	SM185S3CC			SM185-3QAI	220	
	460/3/60	7½		ZR94KC-TFD	SM090S4VC	11/8 x 3/4	Internal overload protector	SM090-4VI	143	7765006
		91/3	CSHA-093K CSHS-093K	ZR108KC-TFD ZR11M3-TWD	SM115S3CC	- 1¾s x ⅓s	Internal thermostat, external overload needed	SM115-4QAI	172	
		10	CSHA-100K CSHS-100K	ZR125KC-TFD ZR12M3-TWD	SM125S4CC			SM125-4QAI	172	
		12½	CSHA-125K	ZR160KC-TWD ZR16M3-TWD	SM160T4CC	1% x 1//s		SM160-4CBI	198	7765028
		14	CSHA-140K CSHS-140K		SM175S4CC			SM175-4QAI	220	
		15	CSHA-150K CSHS-150K	ZR190KC-TWD	SM185S4CC			SM185-4QAI	220	

¹ Code Nos. ending "QAI" include welded sight glas, oil equalization port, brazed connections, and mounting bracket. Code Nos. ending in "VI" and "CBI" are same as "QAI" but exclude the mounting bracket.

Danfoss offers a full line of scroll compressors from 2 to 30 tons. For any product not listed above, please visit http://bit.ly/coolselect or contact counter personnel or Danfoss Refrigeration at 1-888-Danfoss.

www.danfoss.us/aftermarket

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary in specifications already agreed.

All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.