



	<b>FFU130HAX1</b>	LBP-MBP	<b>115V</b>	<b>134a</b>
<b>Specifications</b>			<b>Usage</b>	
Approximate H. P.	1/3+		Drinking Water Coolers	
Starting Torque	High		Dehumidifiers	
Refrigerant	134a		Ice Machines	
Evaporator Temperature	Low/Med		Reach In Refrigerators	
Evaporator Temperature	-31° to 23°F		Beer Coolers	

<b>LBP Performance</b>					
<b>Temperature °F</b>	-31	<b>-10</b>	-22	5	14
<b>Capacity BTU/Hr</b>	517	<b>1,250</b>	777	2,024	2,607
<b>Power W</b>	167	<b>260</b>	204	336	382
<b>Current Amps</b>	3.64	<b>4.05</b>	3.80	4.48	4.76
<b>Temperature °C</b>	-35	<b>-23.3</b>	-30	-15	-10
<b>Capacity Kcal/Hr</b>	130	<b>315</b>	196	510	657
<b>MBP Performance</b>					
<b>Temperature °F</b>	14	<b>23</b>	32	45	50
<b>Capacity BTU/Hr</b>		<b>3,279</b>			
<b>Power W</b>		<b>428</b>			
<b>Current Amps</b>		<b>5.06</b>			
<b>Temperature °C</b>	-10	<b>-5</b>	0	7.2	10
<b>Capacity Kcal/Hr</b>		<b>826</b>			
<b>LBP Rating</b>	<b>ASHRAE</b>	<b>Rating Point (bolded above)</b>	<b>HBP Rating</b>	<b>N/A</b>	
Condensing	130°F		Condensing	N/A	
Evaporator	-10°F		Evaporator	N/A	
Return Gas	90°F		Return Gas	N/A	
Ambient	90°F		Ambient	N/A	
Liquid Temp.	90°F		Liquid Temp.	N/A	

<b>Material</b>	<b>Part number</b>	<b>Description</b>	<b>Compressor Cross Ref.</b>	
Compressor	513200620	FFU130HAX1	Model	Appl.
Relay	513516053	Current relay		
Overload	513554617	MRT 26ADK-5590		
Start Cap	513556535	378-454 mfd / 165V		
Grommet	2221003			
Sleeve	2222015			

**EMBRACO NORTH AMERICA, INC.**  
1610 Satellite Blvd. Suite B, Duluth Ga, 30097 Phone: 678-805-3074