

	NJ9238GK	MBP	230 V	404A
Specifications Approximate H. P. 1 1/2 Starting Torque High Refrigerant 404A Evaporator Temperature Med Evaporator Temperature '-4° to 32°F			Usage Drinking Water Coolers Dehumidifiers Ice Machines Reach In Refrigerators Beer Coolers	

MBP Performance					
Evaporator Temp.°F	-4	5	14	20	32
Capacity BTU/Hr	5,432	7,242	9,234	10,743	13,755
Power W	1,413	1,598	1,793	1,908	2,213
Current Amps	6.57	7.41	8.30	8.83	10.24
Evaporator Temp.°C	-20	-15	-10	-6.7	0
Capacity Kcal/Hr	1,369	1,825	2,327	2,707	3,466

LBP Rating	Rating Point (Bolded above)	MBP Rating	ASHRAE
Condensing		Condensing	130°F
Evaporator		Evaporator	20°F
Return Gas		Return Gas	95°F
Ambient		Ambient	95°F
Liquid Temp.		Liquid Temp.	115°F

Material	Part number	Description	Compressor Cross Ref.
Compressor	943RJ11	NJ9238GK	Model Appl.
Relay	1253015	RVA4AL3C-649	
Overload	2297024	GA3RNU0002	
Start Cap	2252274	130-156 mfd / 330V	
Run Cap	2253314	30 mfd / 440V	
Electrical box	1262271	1272271	
Grommet		2221004	
Sleeve		2222016	

EMBRACO NORTH AMERICA, INC.
1610 Satellite Blvd. Suite B, Duluth Ga, 30097 Phone: 678-805-3074