

embraco	NT6217GKV	MBP-HBP	208-230	404A
Specifications Approximate H. P. 3/4 Starting Torque High Refrigerant 404A Evaporator Temperature Med/High Evaporator Temperature -4° to 50°F			Usage Drinking Water Coolers Dehumidifiers Ice Machines Reach In Refrigerators Beer Coolers	

LBP Performance 208v					
Temperature °F	14	23	32	45	50
Capacity BTU/Hr	3,781	4,648	5,647	7,332	8,048
Power W	750	825	900	1,007	1,048
Current Amps	4.55	4.90	5.26	5.80	6.00
Temperature °C	-10	-5	0	7.2	10
Capacity Kcal/Hr	953	1,171	1,423	1,848	2,028

LBP Rating		Rating Point (Bolded above)	HBP Rating	
Condensing	130°F		Condensing	130°F
Evaporator	-10°F		Evaporator	45°F
Return Gas	90°F		Return Gas	95°F
Ambient	90°F		Ambient	95°F
Liquid Temp.	90°F		Liquid Temp.	115°F

Material	Part number	Description	Compressor Cross Ref.	
			Model	Appl.
Compressor	922ND04	88-108 mfd / 330v		
Relay	2283055			
Overload	2321128			
Start Cap	2252327			
Run Cap	N/A			
Grommet	2221004			
Sleeve	2222016			

EMBRACO NORTH AMERICA, INC.
 2800 Vista Ridge Dr. Suite 100, Suwanee Ga, 30024 Phone: 678-804-1337