

# New Product

## Adjustable Pressure Controls

**SAGInoMIYA®**

### Features

- Designed with contractor input
- Large connector area
- High visibility contrast scale
- Fail-safe bellows available
- Durable, rust proof plastic cover
- Universal mounting bracket
- Snap action switch
- Easy to maintain and access contacts with 24 FLA rating
- Direct replacements for most competitor controls
- Fingertip reset and test for contact operation



SNS-C1C106YQ13



DNS-C1D306YMQ3

Item ID	Operating Pressure (low side/high side)	Reset	Contact System	Range PSI (Low Side/ High Side)	Differential kgf/cm <sup>2</sup> (Low Side/ High Side)	Max Working Pressure kgf/cm <sup>2</sup> (Low Side/High Side)	Direct Replacement For
SNS-C1C106YQ13	Off at 404/ on at 607	Automatic	SPDT	-711 to 85	0.6 to 4	15	060-5231
SNS-C1C106YM2Q2	Off at 28.4psi	Manual	SPDT	-711 to 85	APPROX 0.1MPa	15	060-5232
SNS-C1C106YQ12	Off at 28.4/ on at 43	Automatic	SPDT	-711 to 85	0.6 to 4	15	060-5233
SNS-C1C106YM2Q1	Off at 28.4	Manual	SPDT	-711 to 85	APPROX 0.1MPa	15	060-5234
SNS-C1C110YQ2	Off at 57/on at 85	Automatic	SPDT	14 to 142	1 to 3	15	060-5231
SNS-C1C110YQ1	Off at 57/on at 85	Automatic	SPDT	14 to 142	1 to 3	15	060-5233
SNS-C1C130YQ11	Off at 284.5/ on at 356	Automatic	SPDT	71 to 427	3 to 10	15	060-5241
SNS-C1C130YQ10	Off at 284.5/ on at 356	Automatic	SPDT	71 to 427	3 to 10	15	060-5242
DNS-C1D306YQ11	Low side: on at 39.8 off at 20/High side: on at 241.8 off at 299	Automatic	DPDT	-711 to 85	(0.6 to 4)(3 to 5)	(16.5)(33)	060-5247
DNS-C1D306YQ10	Low side: on at 39.8 off at 20/High side: on at 241.8 off at 299	Automatic	DPDT	-711 to 85	(0.6 to 4)(3 to 5)	(16.5)(33)	060-5248
DNS-C1D306YMQ3	Low side: on at 39.8 off at 20/High side: on at manual off at 299	Manual	DPDT	-711 to 85	(0.6 to 4)(3 to 5)	(16.5)(33)	060-5249
DNS-C1D306YMQ2	Low side: on at 39.8 off at 20/High side: on at manual off at 299	Manual	DPDT	-711 to 85	(0.6 to 4)(3 to 5)	(16.5)(33)	060-5250